

NGT AR Voice transceiver

The NGT AR Voice provides reliable High Frequency (HF) communication and is specially designed for easy installation and mobile use in vehicles. While incorporating Codan's leading-edge HF radio technology, this transceiver also features a user-friendly handset, advanced calling features and *Easitalk* as standard. Extensive Codan Automated Link Establishment (ALE) capabilities (where permitted) and GPS are optional.

KEY FEATURES

Innovative handset

The handset can access all programming procedures in a convenient and consistent manner. It provides an advanced interface, more efficient operation and easier network management.

The handset supports varied requirements ranging from traditional manual voice operation, to sophisticated ALE-reliant calling procedures.

Users can program channels, functions and addresses into the handset to meet their own requirements. These functions

can then be accessed via a series of hot keys. A built-in address book can store up to 100 addresses that can be easily retrieved via the menu.

The handset may be mounted in any position that makes viewing easier. The handset provides a comprehensive display of information.

Easitalk

The NGT AR Voice uses Digital Signal Processing techniques to process received audio signals to minimise the effect of interference and reduce noise. *Easitalk* is simple to operate and

extensive testing has shown that its performance is not affected by the language of the user.

RFDS emergency tone call

The NGT AR Voice has an emergency calling facility. A distress signal can be sent automatically to selected stations.

Smart monitoring

A variety of channels can be monitored while the radio is muted, and calls can be received on any of the channels being scanned.

OTHER FEATURES

Multiple channels

The NGT AR Voice has a capacity for 400 channels.

High dynamic range Rx

The high dynamic range of the NGT receiver provides better reception in difficult conditions.

Voice encryption

The optional *Voice Encryptor* provides communication security (COMSEC) and enables users to communicate sensitive information in confidence, without complicated setup procedures. It also provides visual confirmation that the conversation is secure.

Testing and protection

All Codan transceivers are fully protected from faults such as antenna damage, overvoltage and reverse polarity, which can

destroy other transceivers. A three year warranty is available to every registered user.

Remote diagnostics/ configuration

With Remote Diagnostics your radio installation can be tested remotely by another station to measure parameters such as signal strength, battery voltage levels and power.

It is also possible to remotely reconfigure most transceiver parameters including a facility to disable the transceiver.

Service and support

Codan customers are supported by our worldwide network of Accredited Service Centres. Regular auditing and training by Codan technical staff ensure the best after sales service.



NGT AR Voice in mobile configuration

ADVANCED FEATURES

Automatic Link Establishment (ALE)

To automatically select the most suitable channel, ALE is available as an option. Codan ALE provides full interoperability with other equipment compliant with FED-STD-1045 ALE.

In addition, Codan transceivers outperform many conventional ALE systems through the use of Codan Automated Link Management (CALM).

CALM provides the following additional capabilities and features:

- Multiple networks can be scanned simultaneously at a scan rate of 8 channels per second. This enables up to 3 times more channels to be scanned in the same time as other ALE systems.
- A profile of channel characteristics is developed over time using a 24 hour based Link Quality Analysis (LQA) database, which has over 7 times more storage capacity and uses a higher data resolution than conventional ALE systems. This significantly reduces sounding activities and enables the transceiver to select a suitable channel at any time of the day from the moment it is switched on.

- The Listen-Before-Transmit capability detects both voice and ALE activities on the channel before initiating ALE. This avoids interfering on channels that are engaged.

BITE

Built-In Test Equipment (BITE) is a process that can be initiated by the user to test and report on certain aspects of the system's performance.

Calling facilities

The NGT *AR Voice* has selective calling (selcall), telephone calling (Phone call) and message paging (Message call). All incoming calls are time-stamped to identify precisely when each call arrived.

Selcall: Selcall gives users more flexibility. An operator can call a single transceiver and only that unit will respond—no more listening to noise while waiting for a call. The called transceiver will also signal that the message has been received.

Emergency Selcall: (Optional) The NGT *AR Voice* has a unique emergency calling facility. A distress signal can be sent automatically to selected stations.

Message call: With Message call you can send or receive text messages of up to 64 characters; an external computer is not required. Messages can be encrypted and successful transmissions will be confirmed.

Phone call: This function enables the transceiver to make telephone calls via suitable bases equipped with a telephone interconnect.

GPS

An optional GPS satellite receiver can be connected to the transceiver, via an RS232 port, to enable the following functions:

- a live display of your current GPS position by latitude and longitude
- transmission of your position to another unit
- the ability to request the position of another unit

When used with tracking software, the GPS option provides a complete tracking system to enhance safety. In addition, a security PIN can be used to scramble GPS data so that positions are available only to authorised users.

SPECIFICATIONS

Frequency range	Transmit: 1.6–30 MHz Receive: 250 kHz – 30 MHz
Channel capacity	400 channels
Operating mode	Single sideband (J3E, USB)
Transmitting power output	100 watts PEP
Primary voltage	12 V DC nominal, negative earth
Primary power	Receive (no signal): 0.7 A Transmit: J3E voice: 6 A J3E two-tone: 10–14 A
Temperature	–30 to +60°C
Size and weight	2011 RF Unit: 210 mm W x 270 mm D x 65 mm H; 3.3 kg 2020 Handset: 65 mm W x 35 mm D x 130 mm H; 0.3 kg
ALE link quality data	24 hours of up to 100 stations and 100 channels using a total of 72675 discrete sets of LQA data
ALE link quality data resolution	Local: 8 bits SINAD, 8 bits BER Remote: 5 bits SINAD, 5 bits BER
Dust	MIL-STD-810F method 510.4
Vibration	MIL-STD-810F method 514.5
Shock	MIL-STD-810F method 516.5
GPS interface	NMEA-0183 (4800 baud, RS232)

OPTIONS / ACCESSORIES

Option	Purpose
CALM	FED-STD-1045 ALE/CALM
E	Emergency call
COMSEC	<i>Voice Encryptor</i>
GPS	GPS interface

Values noted are typical. Equipment descriptions and specifications are subject to change without notice or obligation. NGT®, CALM® and Easitalk® are registered trademarks of Codan Limited.

Head Office

www.codan.com.au

12-20151-EN Issue 3: 11/04

Codan Limited
ABN 77 007 590 605
81 Graves Street
Newton SA 5074
AUSTRALIA
Telephone +61 8 8305 0311
Facsimile +61 8 8305 0411
asiasales@codan.com.au

Codan Limited
ABN 77 007 590 605
105 Factory Road
Oxley Qld 4075
AUSTRALIA
Telephone +61 7 3716 6333
Facsimile +61 7 3716 6350

Codan (UK) Ltd
Gostrey House
Union Road
Farnham Surrey GU9 7PT
UNITED KINGDOM
Telephone +44 1252 717 272
Facsimile +44 1252 717 337
uksales@codan.com.au

Codan US, Inc.
8430 Kao Circle
Manassas VA 20110
USA
Telephone +1 703 361 2721
Facsimile +1 703 361 3812
ussales@codan.com.au



CODAN

